# R615DC416UL
# DC Rack Mount CCTV Power Supply

Rev. R615DC416UL_12282011

## Overview

R615DC416UL

This Altronix DC Rack Mount CCTV Power Supply provides 6-15VDC distributed via sixteen (16) fuse protected outputs for powering CCTV cameras, heaters and other video accessories.

## Specifications

### Input:
- 115VAC, 50/60Hz, 0.9 amp.

### Output:
- Sixteen (16) fuse protected outputs.
- 6-15VDC @ 4 amp total output current. *(0.25 amp per device, 3.5 amp max.)*
- Outputs are rated @ 3.5 amp.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.

### Electrical:
- Operating temperature: 0º C to 49º C ambient.
- 9-23 BTU/Hr.
- System AC input VA requirement: 103.5VA.

### Mechanical:
- 2U rack mount chassis for use in standard EIA 19” rack.
- Enclosure Dimensions (H x W x D approx.): 3.26” (83mm) x 19.125” (486mm) x 8.5” (216mm)
- Product weight (approx.): 13.75 lbs. (6.24 kg.).
- Shipping weight (approx.): 14.75 lbs. (6.69 kg.).

### Features:
- Sixteen (16) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.
- Spare fuses provided.

## Agency Approvals

UL Listed for Commercial CCTV Equipment (UL 2044).

CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

## ***Enclosure Dimensions*** *(H x W x D) (approximate)*:

3.26” (83mm) x 19.125” (486mm) x 8.5” (216mm)